

GASGUARD CO₂

CARBON DIOXIDE SENSOR



Key Features

- CO₂ specific infrared sensor technology
- Industry standard linear 4/20 mA output
- Corrosion, weather, and chemical resistant sensor enclosures
- Sensor designed to adapt to any harsh environment from -60°F to +120°F
- Accurately monitor OSHA's PEL and STEL setpoints for personnel protection
- Real-time continuous monitoring
- 0-3% range (0/30,000 ppm) allows setpoints at both critical levels (0.5% & 3.0%)
- 2-year warranty

Industrial strength CO₂ monitoring...for any harsh environment

The GasGuard CO₂ utilizes proven infrared sensor technology for fast and accurate leak detection. With no moving parts and no cells to replace, the GasGuard CO₂ provides real-time continuous monitoring and inexpensive long term operating costs.

The GasGuard CO₂ is carbon dioxide specific, so false alarms from floor cleaners and food off-gassing is non-existent. The output signal is also not affected by moisture or drastic temperature variations such as washdowns, defrost cycles, etc.

The GasGuard CO₂ provides an industry standard linear 4/20 mA output signal compatible with most gas detection systems and PLCs. The high-quality polycarbonate or optional stainless steel enclosures offer excellent chemical corrosion protection and high impact resistance.

Applications

- Wineries
- Food Processing areas
- Indoor Air Quality
- Bottling Plants
- Breweries
- Refrigeration Systems
- Perimeter Monitoring
- Chemical Plants

Benefits

- Versatile for any application
- Low cost
- Simple operation
- Rugged and reliable



The standard **GasGuard CO₂** sensor comes equipped with a corrosion proof enclosure and adaptive temperature control designed to work anywhere. With only one sensor for any application; designing, ordering, and maintaining your CO₂ monitoring system is easy. The 0/3% range (0/30,000 ppm) is broad enough to handle OSHA's recommended alarm levels (0.5% and 3.0%), providing plenty of upper range detection for high output systems.

Designed "Food Industry" tough

The **GasGuard CO₂** is prepared to survive in just about any harsh industrial condition. Every circuit board is sealed forever in potting compound, which protects electronic components and copper tracing from corrosion. A specially vented chemical-resistant polycarbonate enclosure protects the sensor from accidental damage, weather, and direct hose-hits from clean-up crews. An 18 ga stainless steel sensor enclosure is also available for applications that require it.

Ordering Information

The **GasGuard CO₂** is delivered calibrated and ready to install. Use the model numbers below to order.

- Order #:** [GG-CO2-1%](#)
[GG-CO2-3%](#) (standard)
[GG-CO2-5%](#)
[GG-CO2-XXX-ST](#) (stainless enclosure)



Standard polycarbonate enclosure



Mounting flanges for easy installation

Splashguard redirects water from hose-hits

Single-screw door latch for easy access

Completely potted circuit board for corrosion protection

SPECIFICATIONS

Due to ongoing research and product improvement, specifications are subject to change

Input Power:

+24 VDC, 350 mA

Detection Principle:

(NDIR) Non-Dispersive Infrared

Detection Method:

Diffusion

Gas:

Carbon Dioxide (CO₂)

Range:

0/1%
 0/3% (standard)
 0/5%

Output Signal:

Linear 4/20 mA (max input impedance: 700 Ohms)

Linearity:

+/- 3% of full-scale

Repeatability:

+/- 3% of full-scale

Response Time:

T50 = less than 30 seconds
 T90 = less than 60 seconds

Accuracy:

+/- 5% of value, but dependent on calibration gas accuracy

Zero Drift:

Less than 1% of full-scale per month, non-cumulative

Span Drift:

Less than 1% of full-scale per month, non-cumulative

Temperature Range:

-60°F to +120°F (-51°C to +49°C)

Humidity Range:

5% to 100% condensing

Wiring Connections:

3 conductor, shielded, stranded, 20 AWG cable (General Cable C2525A or equivalent) up to 1500 ft

Terminal Block Plugs (Field Wiring):

12-26 AWG, torque 4 lbs-in

Enclosure:

Injection-molded, washdown-duty polycarbonate sensor housing with hinged lid and captive screw. For non-classified areas. Optional 316 18 GA, NEMA 3RX washdown-duty stainless steel housing with hinged lid and captive screw. For non-classified areas

Dimensions:

7.5" high x 6.5" wide x 3.75" deep

Weight:

3 lbs

Certification:

ETL listed to UL standard 61010-1, and CSA standard C22.2 No. 61010-1-12

Warranty:

2 years

