

SB-EV1

EMERGENCY VENTILATION SWITCH



Key Features

- 40 mm push/pull latching mushroom pushbutton switch
- Tamper-proof clear switch cover
- IP66/NEMA 4 weatherproof design for outdoors or washdown environments
- 120 VAC or 24 VDC
- Mounting flanges for wall mounting
- Solution for compressor room emergency ventilation applications
- 2-year warranty

Weatherproof Emergency Ventilation pushbutton switch.

Emergency pushbutton switches are an important part of any control system. They are ideal for protecting personnel and property, allowing the user to press the buttons for emergency ventilation control and pressure control, in addition to triggering the relays through the gas detection system.

The Emergency Ventilation switches can be used with 24 VDC or 120 VAC, and have two sets of 1.5A contacts. The Tamper-proof flip-cover meets most new codes, including IAR-2 2014.

The switches are housed in a durable NEMA 4 polycarbonate enclosure, able to withstand weather and washdown environments for indoor or outdoor mounting applications. Mounting flanges are also included for easy installation.

SPECIFICATIONS

Due to ongoing research and product improvement, specifications are subject to change

CONTACTS RATING: 1.5A, 120 VAC or 24 VDC

ENCLOSURE: Polycarbonate, IP66/NEMA 4

OPERATING TEMPERATURE: -40°F to +150°F

MOUNTING PLATE: Powder coated aluminum

ACTUATOR: Pull to release, mushroom 40 mm

MECHANICAL DURABILITY: 500,000 cycles

ILLUMINATION: Non-illuminated

DIMENSIONS: 6.35" high x 4.42" wide x 4" deep

LISTING: UL, CE

Configurations

All pushbutton switches are pre-installed in their enclosures with tamper-proof cover.

Order #: [SB-EV1](#)

Emergency Ventilation pushbutton switchbox, tamper-proof flip-cover, NEMA 4 enclosure. 1 set of NC contacts, 1 set of NO contacts.



ANSI / IAR 2-2014:

6.12 Emergency Control Switches

6.12.2 Emergency Ventilation Control Switch. A clearly identified control switch for emergency ventilation with a tamper-resistant cover shall be located outside the machinery room and adjacent to the designated principal machinery room door. The switch shall provide "ON/AUTO" override capability for emergency ventilation. The function of the switch shall be clearly marked by signage near the controls.

Example Wiring Diagram (Normal state is the Open position)

